

IC5100

Looking for the most competitive product?



GSM/GPRS, CDMA



9F Yohyun B/D 242-29, Nonhyun-Dong, Gangnam-Gu, Seoul, 135-830, KOREA
TEL:82-2-545-2630 FAX:82-2-545-0190
<http://www.bitelpos.com> E-mail:bitel@bitelpos.com

Specifications of IC5100

MODEL	IC 5100 (Wireless)
CPU	Mips 32bits Clocked at 96Mhz
FLASH	8MB Flash Program ROM
SDRAM	16MB of working RAM (Option)
SRAM	2MB SRAM with battery backup
RTC	Real time Clock (Battery Operated)
LCD	Graphics LCD Display 128x64 Dots / Icon display
PIEZO BUZZER	Used PWM Generator (Various Sound Selection)
BATTERY	Lithium Ion Battery (7.2V)
MODEM	GSM / GPRS modem or CDMA modem module
USB/RS-232	USB2.0/ Up to 460,800bps (One General Purpose Serial Port)
MSR	ISO 7811 Track 1&2 (2&3 is Option)
PRINTER	Thermal Line Printing Number of Dots 384 Dots Resolution 8 Dots/mm Printing Speed 75mm/s
A/D Converter	Internal 6 Channel A/D
IC CARD	Smart card with 2SAM socket
POWER SUPPLY	85 to Volt AC 50/60Hz SMPS Free Voltage AC Adapter